

Basket Webservice / Update API

? Introduction

We offer a web service API for the automated processing of shopping carts. This allows for the subsequent adjustment of already existing baskets. For access, each user receives an Access Token and a User ID, which are provided via the frontend.

? Authentication

The following headers are required to access the API:

Header	Description	Type
Content-Type	The Content-Type of the request	String
X-Network-ID	Network ID: typically <code>-1</code> for cross-client (multi-tenant) API	Integer
X-Auth-Token	Your Access Token (visible in the frontend)	String
X-Auth-ID	Your User ID (visible in the frontend)	Integer

? Endpoints

- **Admin:** `https://SUBDOMAIN.de/ws/V6/admin/JSON/Baskets`
 - **Advertiser:** `https://SUBDOMAIN.de/ws/V6/advertiser/JSON/Baskets`
-

? Example (cURL)

```
curl -X PUT -H "Content-Type: application/json" -H "X-Network-ID: -1" -H "X-Auth-Token: AUTH-TOKEN" -H "X-Auth-ID: USER-ID" -d '[{"basket_item_id": 76041, "amount": 2, "status": "0", "additional": {"variable1": "text", "variable2": 1}}]'  
https://SUB.DOMAIN.DE/ws/V6/admin/JSON/Baskets
```

? Body Parameters

Parameter	Description	Data Type	Required
basket_item_id	Unique ID of the basket item	Integer	☐ Yes
amount	Quantity of the basket item	Integer	No
price	Net price of the basket item	Float	No
status	Status of the order: 0 = open, 1 = confirmed, 2 = canceled	Integer	☐ Yes
turnover	Order value in campaign currency	Float	☐ Yes
additional	Additional information regarding the basket item	JSON	No

Example Request

Headers:

HTTP
□ □

```
Content-Type: application/json
X-Network-ID: -1
X-Auth-Token: ACCESS-TOKEN
X-Auth-ID: USER-ID
```

Body:

JSON
□ □

```
[
  {
    "basket_item_id": 76041,
    "amount": 1,
    "status": "1",
    "additional": {
      "variable1": "text",
```

```
        "variable2": 1
      }
    }
  ]
```

Revision #2

Created 18 May 2026 10:50:53 by Stefanie Goede

Updated 18 May 2026 10:54:08 by Stefanie Goede